



BATTERYcharge 7PIN | PORTABLE | Type 2

Charging Cable for electric and plug-in hybrid vehicles




6/10/16 Ampere

Variable charging currents of 6A/10A/16A meet individual charging requirements



1.3/2.2/3.6 kWh

Variable charging rates of 1.3/2.2/3.6 kWh meet individual charging requirements



5m cable length

Ergonomic handles for optimal handling and a cable length of 5 meters



Charge at home and on the move

Ergonomic handles for optimal handling and a cable length of 5 meters



Drive with OSRAM into a more emission-free future

Discover the world of electric driving with OSRAM. Charge your fully electric or plug in hybrid type 2 vehicle from any 32A (1 phase) charging unit or station fitted with a type 2 connection point. The charging cable is equipped with ergonomic handles for optimal handling and has a cable length of 5 meters. It is suitable for use at public charging stations and at home. In addition, the charging cables are equipped with dust protection caps and tested for water resistance according to IP65 and shock resistance according to IK10. Even when connected, the electrical contact points are protected against the ingress of dust and splash water in accordance with IP65 and IK10. The scope of delivery also includes a durable, compact storage bag to neatly store the cable after charging. In addition, the product

is TÜV and CE certified and comes with a 2-year
guarantee*

Technical data

Product information

Storage Case	Yes
Vehicle Charger Type	Type2
Charging Point Charger Type	Socket


General Product Information

Global order reference	OPC20A05
------------------------	----------

Electrical Data

Nominal wattage	1300 W /2200 W /3600 W
Nominal voltage	240 V
Nominal current	6 A /10 A /16 A

Physical Attributes & Dimensions



Length	5000 mm
Width	120.0 mm
Height	120.0 mm

Lifetime Data

Guarantee	2 years
-----------	---------

Additional product data

Operating Temperature	-25 +45 °C
-----------------------	------------

Certificates & standards

Type of protection	IP65
Standards	TÜV / CE

Product datasheet

IK Class	IK10
----------	------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	542fed56-27b1-425b-a4a9-2a4fce914aac

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899624092	BATTERY charge 7PIN PORTABLE Type 2	Sleeves 1	305 mm x 200 mm x 92 mm	5.61 dm ³	4110.00 g
4052899624160	BATTERY charge 7PIN PORTABLE Type 2	Shipping carton box 4	436 mm x 388 mm x 352 mm	59.55 dm ³	17320.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

Application advice:For more detailed application information and graphics please see product datasheet and the user instruction.*for precise conditions please refer to:
www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

